

Minebea Intec Combics 2

Complete Scale



Application Note:

Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing, averaging, totalizing

Standard Features

- Amber backlit LCD display, 0.8 in, 13 segment
- External calibration routine
- RS-232C
- Numeric keypad (with two IDs) for entering identifier codes and preset tares
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer specific data records
- Two scale connections, analog or digital

Part Number/Price

RLWS PN	Minebea PN	Dimensions	Capacity	Readability	Est. Weight	Price
Mild Steel with CAISL2-U						
156409	CAW2P1U-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	10 ft	Consult
156414	CAW2P1U-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	10 ft	Consult
156420	CAW2P1U-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	10 ft	Consult
156423	CAW2P1UR-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	10 ft	Consult
Stainless Steel with CAIS2-U						
156424	CAW2S1U-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	10 ft	Consult
156425	CAW2S1U-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	10 ft	Consult
156426	CAW2S1U-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	10 ft	Consult
156427	CAW2S4UR-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	10 ft	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	Consult
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	Consult
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	Consult
171727	YDH12CWSUS	Bench mount bracket	Consult

Specifications

Supply Voltage:

9V

Power Requirements:

120-240 VAC, 17 W / 23 VA maximum

Indicator Housing:

AISI 304 stainless steel

Indicator Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in (302.3 x 188 x 89 mm)

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Net Weight:

5 lb (2.27 kg)

Warranty:

Two-year limited warranty

Accessories: one-year limited warranty