

# Intercomp CS™ 200

## Specifications

**Resolution:**

14 bit A/D delivers more than 16,000 internal counts

**Controls:**

Zero, backlight, on/off

**Display:**

0.5 in (12 mm) 4-digit LCD

**Power:**

Standard: one 9V disposable alkaline dry cell, 300 hours

Optional: Rechargeable nickel cadmium cell, 20 hours continuous with backlight

**Enclosure:**

Weatherproof ABS plastic case

**Auto Shut-off:**

Low battery, or after 5 minutes without use

**Accuracy:**

±0.1% of applied load

**Temperature**

Operating +15° F to 122° F (-10° C to 50° C)

**Nominal Overload:**

200% of capacity

**Maximum Overload:**

500% of capacity

**Warranty:**

One-year limited warranty

**Approvals:**

CE



## APPROVALS



## Standard Features

- Lightweight and compact
- Digital calibration
- Auto shut-off
- lb/kg selectable
- Peak hold feature
- Display with backlight

## Part Number/Price

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
<b>CS200 (9V alkaline battery included):</b>			
43734	CS200, 25 lb x 0.01 lb (12.5 kg x 0.01 kg)	2 lb	Consult
43735	CS200, 50 lb x 0.02 lb (25 kg x 0.01 kg)	2 lb	Consult
43736	CS200, 100 lb x 0.05 lb (50 kg x 0.02 kg)	2 lb	Consult
43737	CS200, 250 lb x 0.1 lb (125 kg x 0.05 kg)	2 lb	Consult
82444	CS200, 500 lb x 0.2 lb (250 kg x 0.1 kg)	2 lb	Consult

