

Minebea Intec Signum Series

Complete Scale

Specifications

Platform Size:

13.8 x 9.5 in (350.5 x 241.3 mm)

Power:

Multi-range, 110-240 V

Operating Temperature:

14°F to 104°F (-10°C to 40°C)

Measurement Technology:

SIWRDCP-Load cell signum regular
 SIWADCP-Mechatronic cell-advanced
 SIWSDCP-Monolythic-supreme

Power:

Multi range, 110-240 V

Cable Length:

Display: 6 ft (1.83 m) approximately

Warranty:

Two-year limited warranty
 Accessories: one-year limited warranty



Standard Features

- The Signum is extremely rugged and resistant, and adapts perfectly to any ambient conditions in an industrial environment
- Compact scale built as custom
- Available in three indicator models - 6, 14 or 17 keys
- Available in three weighing technologies - load cell, mechatronic or monolithic
- Resolution 35,000 d to 350,000 d
- Built-in motorized calibration weight (Signum Supreme)
- RS-232 output
- IP65

Weighing Technology	Indicator Options	Capacity	Readability	Included
SIWRDCP (Load Cell)	Applications level 1 - Tare, Zero, Weight	3, 6, 15, 35, and 60 kg	30,000 d	IP65, RS-232, detachable display
SIWADCP (Temperature Compensated Load Cell)	Toggle OR Application level 3 - Tare, Zero, Counting, Checkweighing, ID's	7, 16, 35 and 65 kg	70,000 d	IP65, RS-232
SIWSDCP (Monolythic)		3, 6, 16 and 35 kg	160,000 d-600,000 d	IP65, RS-232, detachable display

Minebea Intec Signum Series

Complete Scale

PRECISION INDUSTRIAL WEIGHING

Part Number/Price

RLWS PN	Minebea PN	Dimensions	# Load Cells	Application Level	Capacity	Readability	Est. Weight	Price
103665	SIWADCP-V3	13.8 x 9.5 in	1	1	7 kg	0.1 g	24 lb	Consult
103666	SIWADCP-V4	13.8 x 9.5 in	1	3	7 kg	0.1 g	24 lb	Consult
105853	SIWADCP-V5	13.8 x 9.5 in	1	3	35 kg	0.5 g	24 lb	Consult
105854	SIWADCP-V6	13.8 x 9.5 in	1	3	65 kg	1 g	24 lb	Consult
103657	SIWRDCP-V7	13.8 x 9.5 in	1	1	6 kg	0.2 g	22 lb	Consult
103658	SIWRDCP-V8	13.8 x 9.5 in	1	1	15 kg	0.5 g	24 lb	Consult
103659	SIWRDCP-V9	13.8 x 9.5 in	1	1	35 kg	1 g	24 lb	Consult
103660	SIWRDCP-V10	13.8 x 9.5 in	1	1	60 kg	2 g	24 lb	Consult
151372	SIWSBBPP-V16	7.1 x 7.1 in	1	1	3 kg	0.01 g	16.5 lb	Consult
151373	SIWSBBPP-V17	7.1 x 7.1 in	1	1	6 kg	0.01 g	16.5 lb	Consult
151374	SIWSDCP-V18	13.8 x 9.5 in	1	1	16 kg	0.1 g	24 lb	Consult
151375	SIWSDCP-V19	13.8 x 9.5 in	1	1	35 kg	0.1 g	24 lb	Consult
151376	SIWRDCP-V20	13.8 x 9.5 in	1	3	6 kg	0.2 g	24 lb	Consult
151377	SIWRDCP-V21	13.8 x 9.5 in	1	3	15 kg	0.5 g	24 lb	Consult
151378	SIWRDCP-V22	13.8 x 9.5 in	1	3	35 kg	1 g	24 lb	Consult
151379	SIWRDCP-V23	13.8 x 9.5 in	1	3	60 kg	2 g	24 lb	Consult
151410	SIWADCP-V24	13.8 x 9.5 in	1	1	16 kg	0.2 g	24 lb	Consult
151411	SIWADCP-V25	13.8 x 9.5 in	1	1	35 kg	0.5 g	24 lb	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
36907	YDP03-OCE	Data printer, statistics and T/D functions, 5 ft Cable (requires 83248)	Consult
31106	6906918	Ribbon	Consult
31103	6906937	Paper	Consult
83248	YCC01-0016M3	Cable, 9.8 ft, 12-Pin round to 25 D-Sub female	Consult
105607	YDH02CISUS	Wall mount bracket	Consult
153218	YDH01PUS	Column for DC platforms, 19 in	Consult
155884	YDH02P	Column to BBP	Consult
155804	YCC05-001M2	RS-232 cable, 25-Pin D-sub male to 9/25-Pin D-sub female	Consult

www.ricelake.com | Phone: 800-472-6703

RICE LAKE

850